



Mainlube Superior Maintenance Lubricants Pty Ltd

14 Underwood Ave, Botany NSW, 2019

Ph 02-9700-0880. ACN No. 001 748 876 Fax 02-9700-0881.

STATEMENT OF HAZARDOUS NATURE

Non Hazardous According to Criteria of Worksafe Australia

MATERIAL SAFETY DATA SHEET MAINLUBE 150

IDENTIFICATION

Product Name:	Mainlube 150
Chemical Name:	E P Gear Lubricant.
Other Names:	Not Applicable
Manufacturer's Product Code:	150
UN Number:	None Assigned
Dangerous Goods Class	None Assigned
Subsidiary Risk[s]:	None Assigned
Hazchem Code:	None Assigned
EPG NO:	None Assigned
Poisons Schedule Number:	None Assigned
Toxic and Hazardous	
Ingredients:	None
Uses:	Automotive Industrial Gear Lubricant

Page 1 of 3
Aug-06

PHYSICAL DESCRIPTION AND PROPERTIES

Colour:	Red.
Appearance:	Red & Tacky Oily Liquid
Form:	Liquid
Boiling Point:	No Data.
Melting Point:	Not Applicable
Vapour Pressure:	mm Hg: <0.01.
Specific Gravity:	kg/L @ 15.0°C: 0.908.
Volatiles:	Not Applicable
Evaporation Rate:	Not Applicable
Vapour Density:	Not Applicable
Odour:	EP Gear Lubricant Smell
Solubility in Water:	Nil @ 20°C

FLASH POINT

Solvent:	Not Applicable
Lubricant residue:	:>250°C
Flammability Limits :	Not Applicable
Auto ignition	
Temperature:	No Data

MATERIAL SAFETY DATA SHEET MAINLUBE 150

OTHER PROPERTIES

Hazardous Polymerisation: Does not occur.

Page 2 of 3
Aug-06

INGREDIENTS

Chemical Name	CAS Number	Proportion
Highly refined mineral oils	64742-65-0	87-90%
Tackifier	-	1.5-3%
Other	Included. On US TSCA Inventory	7-10%
Liquid Red Dye, B	71819-51-7	<0.06%

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Acute:

Swallowed: If swallowed and person is conscious give water or milk. Ingestion or subsequent vomiting may result in its aspiration which could cause pneumonitis.

Skin: Prolonged or frequent contact may cause irritation or skin cracking.

Eyes: May cause moderate eye irritation.

Inhaled: Vapour or mist at concentrations exceeding ACGIH TLV may be irritating to the respiratory tract.

Chronic:

LC 50: No Data
LD 50: No Data

FIRST AID:

Swallowed: Do not induce vomiting. Aspiration of the fluid may cause lung injury (pneumonitis). Call a Doctor immediately.

Skin: Wash thoroughly with soap and water.

Eyes: Flush with water for 15 minutes, at least with eyelids open.

Inhaled: If respiratory irritation occurs move person to fresh air. If irritation continues call a Doctor.

FIRST AID FACILITIES:

ADVICE TO DOCTOR:

Refer First Aid above.

PRECAUTIONS FOR USE:

Exposure Standards: The ACGIH TLV for mineral oil mists is 5mg/m³ for a daily 8 hours exposure.

Engineering Controls: No Applicable

Personal Protection: Not generally required. Avoid prolonged or frequently repeated contact. Wash skin thoroughly with soap and water after contact. Preferred to use safety glasses and neoprene or nitrile rubber gloves for frequent contact.

Flammability: No unusual fire and explosion hazards.

MATERIAL SAFETY DATA SHEET MAINLUBE 150

SAFE HANDLING INFORMATION

Page 3 of 3
Aug-06

Storage and Transport:	Store in steel or HDPE plastic drums. Store away from strong oxidising agents. Refer Dangerous Goods Class 5:1
Storage Temperature:	Store in a cool dry place.
UN Class:	None Assigned.
Packaging Group:	None Assigned.
UN Number:	None Assigned.
EPG Number:	None Assigned.
Correct Shipping Name:	E P Gear Lubricant.
Spills and Disposals:	Absorbents such as cat litter, clays and rags to clean up spills. Dispose of absorbent in approved disposal containers.
Fire/Explosion Hazard:	Not a fire hazard. Auto ignition temperature is in excess of 450°C. Should fire occur, however, use dry chemical, foam or carbon dioxide to extinguish.
Decomposition Products:	High temperature thermal decomposition may promote formation Oxides of Carbon, Nitrogen, Sulphur and Phosphorus.
Hazchem Code:	Not Applicable
Extinguishant:	Use dry chemical, foam or carbon dioxide.

DANGER OF VIOLENT REACTION OR EXPLOSION: No

Protective Clothing;	Applicable to degree of fire.
Appropriate Measures;	No Data
Evacuate;	Not Usually

OTHER INFORMATION:

150 E P Gear Lubricant is not expected to present environmental problems other than those associated with oil spills.

CONTACT POINT:

Mr Steve Simmonds
Mainlube Superior Maintenance Lubricants Pty Ltd.
14 Underwood Ave, Botany. NSW, 2019, Australia
Ph 02-9700-0880. Fax 02-9700-0881.
Mob 0412-644-244.

24 Hour Emergency Tel No. Above Mobile Phones

Emergency Services

Dial 000

We believe the statement, technical information and recommendation contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assure no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.