



Mainlube Superior Maintenance Lubricants Pty Ltd

189-191 Botany Road Waterloo, NSW, 2017

Ph 02-9310-3433.

ACN No. 001 748 876

Fax 02-9310-3503.

STATEMENT OF HAZARDOUS NATURE

Non Hazardous According to Criteria of Worksafe Australia

MATERIAL SAFETY DATA SHEET MAINLUBE 162

IDENTIFICATION

Page 1 of 3
Aug-06

Product Name:	Mainlube 162
Chemical Name:	Power Transmission Lubricant.
Other Names:	None Assigned.
Manufacturer's Product Code:	162
UN Number:	None Assigned.
Dangerous Goods Class	None Assigned.
Subsidiary Risk[s]:	None Assigned.
Hazchem Code:	None Assigned.
EPG NO:	None Assigned.
Poisons Schedule Number:	None Assigned.
Toxic and Hazardous	
Ingredients:	None.
Uses:	Powershift Transmission Fluid

PHYSICAL DESCRIPTION AND PROPERTIES

Colour:	Red.
Appearance:	Oily Liquid
Form:	Liquid
Boiling Point:	>300 °C
Melting Point:	Not Applicable
Vapour Pressure:	Not Applicable
Specific Gravity:	kg/L @ 15.0 °C : 0.898
Volatiles:	Not Applicable.
Evaporation Rate:	Not Applicable.
Vapour Density:	Not Applicable.
Odour:	Oily Odour
Solubility in Water:	Nil @ 25 °C

FLASH POINT

Solvent:	Not Applicable
Lubricant residue:	>250 °C
Flammability Limits :	Not Applicable
Auto ignition	
Temperature:	No Data

MATERIAL SAFETY DATA SHEET MAINLUBE 162

OTHER PROPERTIES

Hazardous Polymerisation: Does not occur

Page 2 of 3
Aug-06

INGREDIENTS

Chemical Name	CAS Number	Proportion
Highly refined mineral oils (Does not contain PCB's)	64742-65-0	82-86%
Other	Include. On US TSCA Inventory	14-18%
Liquid Red Dye, B	71819-51-7	0.02

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Acute:

Swallowed: If swallowed and person is conscious give water or milk. Ingestion or subsequent vomiting may result in its aspiration which could cause pneumonitis.

Skin: Prolonged or frequent contact may cause irritation or skin cracking.

Eyes: May cause moderate eye irritation.

Inhaled: Vapour or mist at concentrations exceeding ACGIH TLV may be irritating to the respiratory tract.

Chronic:

LC 50: No Data
LD 50: No Data

FIRST AID:

Swallowed: Do not induce vomiting. Aspiration of the fluid may cause lung injury (pneumonitis). Call a Doctor immediately.

Skin: Wash thoroughly with soap and water.

Eyes: Flush with water for 15 minutes, at least with eyelids open.

Inhaled: If respiratory irritation occurs move person to fresh air. If irritation continues call a Doctor.

ADVICE TO DOCTOR:

Refer First Aid above.

PRECAUTIONS FOR USE

Exposure Standards: The ACGIH TLV for mineral oil mists is 5mg/m³ for a daily 8 hours exposure.

Engineering Controls: As for oil mists.

Personal Protection: Avoid prolonged or frequently repeated contact. Wash skin thoroughly with soap and water after contact. Use safety glasses and neoprene or nitrile rubber gloves for frequent contact.

Flammability: Product is not classed flammable. Flash Point greater than 190°C
Product may support combustion. Do not store with strong oxidants.

MATERIAL SAFETY DATA SHEET MAINLUBE 162

SAFE HANDLING INFORMATION

Page 3 of 3
Aug-06

Storage and Transport:	Store in steel or HDPE plastic drums. Store away from strong oxidising agents. Refer Dangerous Goods Class 5:1
Storage Temperature:	Store in a cool dry place.
UN Class:	None Assigned
Packaging Group:	None Assigned
UN Number:	None Assigned
EPG Number:	None Assigned
Correct Shipping Name:	Power Transmission Lubricant.
Spills and Disposals:	Absorbents such as cat litter, clays and rags to clean up spills. Dispose of absorbent in approved disposal containers.
Fire/Explosion Hazard:	Not a fire hazard. Auto ignition temperature is in excess of 450 °C. Should fire occur, however, use dry chemical, foam or carbon dioxide to extinguish.
Decomposition Products:	High temperature thermal decomposition may promote formation Oxides of Carbon, Nitrogen, Sulphur and Phosphorus.
Hazchem Code:	Not Applicable.
Extinguishant:	Dry chemical, foam or carbon dioxide.

DANGER OF VIOLENT REACTION OR EXPLOSION: No

Protective Clothing;	Applicable to degree of fire.
Appropriate Measures;	No Data
Evacuate;	Not Usually

OTHER INFORMATION:

Power Transmission Lubricant is not expected to present environmental problems other than those associated with oil spills.

CONTACT POINT:

Mr Steve Simmonds, Mr Rob Simmonds,
Mainlube Superior Maintenance Lubricants Pty Ltd.
189-191 Botany Road Waterloo, NSW, 2017, Australia
Ph 02-9310-3433. Fax 02-9310-3503.
Mob 0412-644-244, Mob 0411-243-150.

24 Hour Emergency Tel No. Above Mobile Phones

Emergency Services

Dial 000

We believe the statement, technical information and recommendation contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assure no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.